

Conductor:
Red copper
Class 5 according to
IEC 60228

Isolation:
thermoplastic
Color code: Numbered black

Carrier:
2 steel elements

Outer sheath:
PVC Noir



PRODUCT INFORMATION

APPLICATION

Suitable for use as a control cable for elevators, transportation systems, and cranes, as well as for hanging control buttons in rack storage facilities. Suitable for use indoors as well as outdoors down to temperatures of -25°C

DESCRIPTION OF THE CABLE

Assemblage: Conductors assembled in parallel.

ELECTRICAL PROPERTIES

Rated voltage: 300/500 V
Trial tension: 2000 V

CHARACTERISTICS



Fire resistance:
IEC 60332-1



Service temperature:
Static: -25°C / +60°C
Dynamic: -25°C / +60°C



Minimum radius of curvature:
12 x Øext




Compliant with the RoHS Directive

Reference Standards:
DIN VDE 0250

Breaking load carrier elements 1400N

PRODUCT REFERENCES

			
BBAP12G1	12 G 1	12,5 (19,5) - 15,5 (28,5)	408
BBAP18G1	18 G 1	15,5 (22,7) - 17,6 (33,4)	590
BBAP25G1	25 G 1	17,5 (27,0) - 21,8 (37,5)	751
BBAP8G15	8 G 1,5	11,5 (21,0) - 15,5 (28,5)	419
BBAP12G15	12 G 1,5	12,5 (22,5) - 16,7 (31,5)	515
BBAP20G15	20 G 1,5	15,5 (26,0) - 21,8 (37,5)	798
BBAP5X15	5 X 1,5	9,0 (18,0) - 14,3 (23,3)	350
BBAP8X15	8 X 1,5	11,5 (21,0) - 15,5 (28,5)	420
BBAP12X15	12 X 1,5	12,5 (22,5) - 16,7 (31,5)	515
BBAP16X15	16 X 1,5	14,5 (22,7) - 18,5 (32,0)	595
BBAP20X15	20 X 1,5	15,5 (26,0) - 21,8 (37,5)	800