


H05-07V2-K

Wire V2-K UL/CSA 1015



Conductor:
Tinned copper
Grade 5 according to:
IEC 60228

Isolation:
PVC
Color: blue, brown, white, gray, brown, black, orange,
red, purple, green/yellow



FT 11/06/15 EN

PRODUCT INFORMATION

APPLICATION

The UL/CSA harmonized cables H05/07V2-K are equipped with a flexible PVC sheath for fixed installation.

ELECTRICAL PROPERTIES

Rated voltage U°/U:	
- H05	300 / 500 V
- H07	450 / 750 V
Style1015	600 V
Test voltage:	3000 V

FEATURES



Fire resistance:
EN 60332-1



Service temperature:
-40 °C / +70° C (90° C)
UL-CSA: -40 °C /+105° C



Minimum radius of curvature:
Fix 4 x Ø
move 15 x Ø



In accordance with the RoHS directive.

Reference standards
UL: AWM style 1015 + MTW; CSA: TEW;
HAR (VDE0281/HD21)

PRODUCT REFERENCES			
			
H05V2-K			
V2K050	0.50	2.5	10
V2K075	0.75	2.7	12.5
V2K1	1	2.8	16
H07V2-K			
V2K15	1.5	3.2	21.8
V2K25	2.5	3.6	32
V2K4	4	4.3	46.5
V2K6	6	4.8	67.2
V2K10	10	6.5	128
V2K25MM	25MM	9.9	291
V2K35	35	11.3	390
X07V2-K			
V2K16	16	8.6	192
V2K50	50	13.5	530
V2K70	70	15.6	755
V2K95	95	17.8	930
V2K120	120	20.8	1175
V2K150	150	22.2	2085