



The LevelOne FEU-0512 is a wire-speed, non-blocking networking device that provides 5 ports of 10/100 Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as a general network port or as a connecting port into a router, server, hub, or another network switch.

PRODUCT INFORMATION

MAIN FEATURES

- Provision of flexibility for the 5 ports 10/100BASE-TX.
- 10/100Mbit/s, Full-Duplex/Half-Duplex, auto-negotiation Automatic MDI/MDIX
- Quick and easy installation
- Support for self-learning and aging of 1K MAC addresses
- Easy ready-to-use installation

CHARACTERISTICS

General	5 × 10/100Mbps
---------	----------------

REPRESENTACIÓN

Packet transfer rate	148800pps
----------------------	-----------

PHYSICAL SPECIFICATIONS

Dimensions (L x W x H mm)	89*86*23mm
Weight (g):	<1KG

SYSTEM SPECIFICATIONS

Standards	IEEE802.3(10BASE-T), IEEE802.3u(100BASE-T), IEEE802.3az Energy Efficient Ethernet
Indicator:	Power, LINK/ACT
Transmission method:	Store- forward
Power input:	5V/0.6A
Rear panel (Gbit/s):	1Gbps
MAC Address Table:	1K
Operating temperature (°C):	0-40°C
Operating humidity:	10%~90%

Order information	FEU-0512
-------------------	----------

Packaging content	FEU-0512 Power Adapter Quick Installation Guide
-------------------	--